

Features and benefits

- Third party certifcation part of a dpm/ gas protection BBA approved jointing system
- Moisture resistant provides excellent resistance to damp ingress
- Excellent Adhesion to damp proof membranes
- Joint integrity stops poured concrete entering the lap joint
- Heath and Safety seals the exposed lap from risk of installer accidents

Product description

VisqueenPro Single Sided Tape is a crossweave glassfibre reinforced tape coated with a high tack aggressive adhesive system.

It is available in roll format 75mm x 25m.

Approvals and standards

- Third party accreditation BBA certifcation
- Quality Management System ISO 9001:2015
- Occupational Health and Safety System ISO 18001:2007
- Environmental Management System ISO 14001:2015

Usage

VisqueenPro Single Sided Tape is used to seal lap joints on damp proof membranes. It can be used internally and externally and is suitable in compressed load applications. The tape can also be used for patch work - when membranes are punctured - and sealing around pipe penetrations.

To be used in conjunction with VisqueenPro Double Sided Jointing tape which bonds the membranes together.

System components

Find your local stockist







Storage and handling

Store in warm, dry and clean environment in its current packaging. The tape should not be exposed to long periods of ultraviolet light. In very cold weather, prior to use ensure that the material is stored in warm conditions above 5°C.

Preparation

Ensure all surfaces are clean and dry. The membrane joint surfaces should be dry and free from contamination such as dust or sand. Ensure the surface and working area is not water logged. Avoid areas of unsupported jointing.

Installation

Jointing - Apply VisqueenPro Double Slded Jointing tape tape to the lap area of the laid sheet starting approximately 50mm from the membrane edge. Apply pressure to the tape to ensure the tape has adhered to the membrane. Remove quick release paper from the tape and overlap the adjoining membrane by minimum 150mm. The membrane lap joints should then be sealed using the VisqueenPro Single Sided Jointing tape lap tape. Once the tape is applied, the completed lap should be well rolled with firm pressure to ensure a complete seal joint has occurred, and continuity with the adjacent sheet has been achieved.

If the membrane is punctured or perforated a patch of the same material should be lapped at least 150mm beyond the limits of the puncture and bonded with Visqueen Pro Double Sided Jointing Tape and sealed with the Pro single sided tape.

Airtight seals should be formed around all service entry points. Visqueen preformed Top Hat Units should be used for sealing service entry pipes. The base of the top hat and the upstand should be bonded using VisqueenPro Double Sided Jointing Tape and sealed with VisqueenPro Single Sided Tape. The upstand should be secured with the supplied jubilee clip.

Usable temperature range

It is recommended that VisqueenPro single sided jointing tape and other system components should be used above 5°C.

Additional information

Ensure product is stored in warm conditions prior to use. In very cold weather, prior to use ensure that the material is stored in warm conditions above 5°C.





Property	Value
Dimensions	75mm x 25m
Application temperature range	5°C to 50 5°C
Tensile strength	240N/cm
Elongation	10%

Health and safety information

Please refer to material safety datasheet.





About Visqueen

The Visqueen name has long been recognised as one of the leading manufacturers of high quality advanced membrane technologies and design based solutions by specifiers, distributors, builders merchants and contractors throughout the UK and Europe.

For further guidance on the Visqueen services shown below, please refer to the relevant section of the Visqueen website (www.visqueen.com) or contact Visqueen Technical Services on +44 (0) 333 202 6800 or enquiries@visqueen.com

Complete Range, Complete Solution



Visqueen Technical Support

Visqueen combine an extensive product portfolio with industry leading levels of service and support which includes guidance over the phone, bespoke CAD drawings to help with complex detailing, electronic NBS specifications and access to a dedicated team of highly knowledgeable and experienced field based Technical Support Managers.

Visqueen Technical Support is available to all our customers including architects, specifiers, distributors, builders merchants, contractors and end users. All of our technical team have been awarded the industry recognised qualification Certificated Surveyor in Structural Waterproofing (CSSW).

Visqueen CPD Seminars

The Visqueen Continuing Professional Development (CPD) Seminars provide up-to-date information on changes within Building Regulations/Building Standards and nationally recognised industry guidance affecting damp proofing, water vapour control, hazardous ground gas protection and below ground structural waterproofing.

The one hour seminars have been produced for design specialists within the construction sector and are delivered by our team of Technical Support Managers.

Visqueen PI designs and special projects

From initial design to the completed project, Visqueen are with you every step of the way. Whether it be hazardous ground gas protection and/or below ground waterproofing protection employing barrier, structurally integral or drained systems, Visqueen can offer professional indemnity (PI) insurance for bespoke Visqueen design solutions.

Visqueen Technical Support Managers work with all stakeholders to provide cost effective Visqueen solutions offering complete peace of mind throughout the construction phase and beyond.

Visqueen Training Academy

Based at our manufacturing facility in Derbyshire, the Visqueen Training Academy is available to support Visqueen customers throughout the UK by providing a wide range of both theory and practical skills related training.

Courses include one day product awareness training for our distributors and builders merchants to help them in their day-to-day jobs, through to intensive three day courses giving detailed hands-on training in the practical skills required for safe and robust product installation.

