SPIT D-Line RED U CLIP 30

Product Code : 923646

DESCRIPTION

- The red finish makes a popular solution for containing red-sheath fire performance cables direct to surface.
- The 23mm width is ideal for popular 2x MICC or FP-cable combinations.
- Certified for 2 hours at 970°C
- Compliant with BS7671 and BS5839-1 requirements
- Non-corrosive coating

TOOLS

- Pulsa 800 (To be used with the flat magnetic pin guide (014642)

SPECIFICATION

- Pre-drilled hole of 5.7mm for screw fixing option
- Complies with requirements of BS5839 part 1 (2002 section 26.2c
- BSEN50200:2000; & BS8434-1:2003
- 20mm wide side-tabs & pliable gauge combines for quick and eas folding
- Smooth & rounded edges, as required by design code BS7671 s522.8.11, to protect soft-skin cables etc (and user friendly!)

DIMENSIONS (mm):



(L) 20mm x (W) 23mm x (H) 8mm (folded) 5.7mm diameter pre-drilled hole in base

PIN SELECTOR GUIDE

- Ensure that the embedment depth is adapted to the recommended load requested for the accessories
- HC6FH can also be used in conjunction with the U clip. See pin size as guide.

PIN SELECTOR GUIDE:		C6-20	C6-25	C6-30	HC6-15	HC6-17	HC6-22	HC6-27	CW6
Concrete C20/25		■	■			■	■		
Concrete C30/37		■				■			
Concrete C40/50					■	■			
Prestressed / Prefabricated concrete					■	■			
Solid Brick			■				■		
Hollow Brick rendered			■				■		
Hollow concrete block			■				■		
Calcium silicate block			■				■		
Steel					■				
Timber									■